

BLUE DOT TAPING

- Super slick
- Great open time
- High bond



| PRODUCT # | 18200 |
|--------------|-------|
| UNIT | CTN |
| SHIP WT. | 47 |
| UNITS/PALLET | 48 |

RED DOT ALL PURPOSE

- Suitable for all finishing applications
- Best for taping and first metal
- High bond



| PRODUCT # | 18040 |
|--------------|-------|
| UNIT | CTN |
| SHIP WT. | 50 |
| UNITS/PALLET | 48 |

TNT TAPING & TOPPING

- Excellent for all finishing applications
- A true one mud system
- Tinted



| PRODUCT # | 18180 |
|--------------|-------|
| UNIT | CTN |
| SHIP WT. | 50 |
| UNITS/PALLET | 48 |

JOINT COMPOUNDS

WHITE DOT ALL PURPOSE

- Excellent for all finishing applications
- Low shrinkage
- Non-tinted



| PRODUCT # | 18100 |
|--------------|-------|
| UNIT | CTN |
| SHIP WT. | 50 |
| UNITS/PALLET | 48 |

GREEN DOT TOPPING

- For second and finish coats
- Low shrinkage
- Easy sanding



| PRODUCT # | 18220 | 18230 |
|--------------|------------|--------|
| DESCRIPTION | Non-Tinted | Tinted |
| UNIT | CTN | CTN |
| SHIP WT. | 50 | 50 |
| UNITS/PALLET | 48 | 48 |

BLACK DOT TOPPING

- For second and finish coats
- Low shrinkage
- Easiest sanding
- Tinted



| PRODUCT # | 18360 |
|--------------|-------|
| UNIT | CTN |
| SHIP WT. | 50 |
| UNITS/PALLET | 48 |

All joint compounds meet ASTM C-475.



JOINT COMPOUNDS

ALL PURPOSE JOINT COMPOUND

- Use for taping, topping and texturing
- Excellent bond and low shrinkage
- Excellent for all applications



| PRODUCT # | 55410 | 18680 | 18720 |
|--------------|----------|---------|--------|
| DESCRIPTION | 1.75 Pt. | 3.5 Qt. | 4 Gal. |
| UNIT | PL | PL | PL |
| SHIP WT. | 18/6 | 14 | 67 |
| UNITS/PALLET | 96 | 96 | 36 |

BLUE DOT LIGHT WEIGHT TAPING

- Easy handling for increased productivity
- Great open time
- Great bond



| PRODUCT # | 18205 |
|--------------|-------|
| UNIT | CTN |
| SHIP WT. | 31 |
| UNITS/PALLET | 64 |

TNT LITE LIGHT WEIGHT TAPING & TOPPING

- Less weight increases ease of finishing and handling
- Low shrinkage
- One mud system decreases waste



| PRODUCT # | 18170 |
|--------------|-------|
| UNIT | CTN |
| SHIP WT. | 39 |
| UNITS/PALLET | 64 |

LIGHT WEIGHT JOINT COMPOUNDS

GREEN DOT LIGHT WEIGHT TOPPING

- Easy handling for increased productivity
- Excellent workability
- Easy sanding and low shrinkage



| PRODUCT # | 18250 |
|--------------|-------|
| UNIT | CTN |
| SHIP WT. | 39 |
| UNITS/PALLET | 64 |

HI LITE MID WEIGHT ALL PURPOSE

- Less weight increases ease of finishing and handling
- Low shrinkage
- One mud system decreases waste



| PRODUCT # | 18380 |
|--------------|-------|
| UNIT | CTN |
| SHIP WT. | 41 |
| UNITS/PALLET | 64 |

SUPER LITE LIGHT WEIGHT ALL PURPOSE

- 40% lighter than conventional joint compounds
- Easy handling for increased productivity
- Excellent workability, easy sanding and low shrinkage



| PRODUCT # | 18080 |
|--------------|-------|
| UNIT | CTN |
| SHIP WT. | 31 |
| UNITS/PALLET | 64 |

All joint compounds meet ASTM C-475.



BLUE LINE

- High mileage
- Fine to medium texture pattern
- Good open time



| PRODUCT # | 14100 |
|--------------|-------|
| UNIT | BG |
| SHIP WT. | 52 |
| UNITS/PALLET | 54 |

BLUE LINE II

- Easy mixing
- Excellent standout
- All texture pattern



| PRODUCT # | 14180 |
|--------------|-------|
| UNIT | BG |
| SHIP WT. | 52 |
| UNITS/PALLET | 54 |

GREEN LINE

- Easy mixing
- Excellent standout
- Medium to heavy texture pattern



| PRODUCT # | 14040 |
|--------------|-------|
| UNIT | BG |
| SHIP WT. | 52 |
| UNITS/PALLET | 54 |

WALL TEXTURES

GREEN LINE II

- Easy mixing
- Great standout and great mileage
- Medium texture pattern



| PRODUCT # | 14135 |
|--------------|-------|
| UNIT | BG |
| SHIP WT. | 52 |
| UNITS/PALLET | 54 |

READY TEX

- Quick, easy professional results
- Convenient for hopper guns
- Great for hand texture applications



| PRODUCT # | 14210 |
|--------------|-------|
| UNIT | CTN |
| SHIP WT. | 53 |
| UNITS/PALLET | 48 |

RED LINE

- Highest mileage
- Easy mixing
- Fast pumping



| PRODUCT # | 14130 |
|--------------|-------|
| UNIT | CTN |
| SHIP WT. | 52 |
| UNITS/PALLET | 54 |



CEILING-TEX PREMIUM

- Ideal for use with production type spray equipment
- Produces an aggregated "popcorn" finish



| PRODUCT # | 10040 |
|--------------|-------|
| UNIT | BG |
| SHIP WT. | 34 |
| UNITS/PALLET | 52 |

CEILING TEXTURES

HOPPER-TEX

- Easy mixing for hopper type equipment or respray applications
- Produces an aggregated "popcorn" finish



| PRODUCT # | 10025 |
|--------------|-------|
| UNIT | BG |
| SHIP WT. | 27 |
| UNITS/PALLET | 54 |

FAST SET 5 LITE

- 5 minute set time
- Easy mixing
- Easy sanding
- · Smooth finish



| PRODUCT # | 22164 |
|--------------|----------|
| DESCRIPTION | 5 Minute |
| UNIT | BG |
| SHIP WT. | 20 |
| UNITS/PALLET | 96 |

FAST SET 20 LITE

- 20 minute set time
- Easy mixing
- Easy sanding
- Smooth finish



| PRODUCT # | 22165 |
|--------------|-----------|
| DESCRIPTION | 20 Minute |
| UNIT | BG |
| SHIP WT. | 20 |
| UNITS/PALLET | 96 |

LIGHT WEIGHT SETTING TYPE COMPOUNDS

FAST SET 40 LITE

- 40 minute set time
- Easy mixing
- Easy sanding
- Smooth finish



| PRODUCT # | 22166 |
|--------------|-----------|
| DESCRIPTION | 40 Minute |
| UNIT | BG |
| SHIP WT. | 20 |
| UNITS/PALLET | 96 |
| | |

FAST SET 90 LITE

- 90 minute set time
- Easy mixing
- Easy sanding
- · Smooth finish



| PRODUCT # | 22167 |
|--------------|-----------|
| DESCRIPTION | 90 Minute |
| UNIT | BG |
| SHIP WT. | 20 |
| UNITS/PALLET | 96 |

All Fast Set Lights are GreenGuard Gold Certified and meet ASTM C-475.



FAST SET 20

- 20 minute set time
- Excellent bond
- Smooth finish
- Harder finish



| PRODUCT # | 22105 |
|--------------|-----------|
| DESCRIPTION | 20 Minute |
| UNIT | BG |
| SHIP WT. | 27 |
| UNITS/PALLET | 96 |
| | |

SETTING TYPE COMPOUNDS

FAST SET 40

- 40 minute set time
- Excellent bond
- Smooth finish
- Harder finish



| PRODUCT # | 22107 |
|--------------|-----------|
| DESCRIPTION | 40 Minute |
| UNIT | BG |
| SHIP WT. | 27 |
| UNITS/PALLET | 96 |

FAST SET 90

- 90 minute set time
- Excellent bond
- Smooth finish
- Harder finish



| PRODUCT # | 22115 |
|--------------|-----------|
| DESCRIPTION | 90 Minute |
| UNIT | BG |
| SHIP WT. | 27 |
| UNITS/PALLET | 96 |

All Fast Sets are GreenGuard Gold Certified and meet ASTM C-475.

HOT CRETE PRIMER

- Premium high solids, high build interior primer
- Excellent alkaline resistance (up to pH 13)
- Built in rust inhibitor



| PRODUCT # | 25100 |
|--------------|--------------|
| UNIT | 4.8 Gal Pail |
| SHIP WT. | 72 |
| UNITS/PALLET | 36 |

CONCRETE FINISHING PRODUCTS

ULTRA FILL

- 90 minute set time
- Excellent adhesion
- Fills voids and patches up to 1" thick or more with one coat
- GreenGuard Gold Certified



| PRODUCT # | 22121 |
|--------------|-------|
| UNIT | BG |
| SHIP WT. | 36 |
| UNITS/PALLET | 54 |

WALLBOARD TAPE

BLUE LABEL WALLBOARD TAPE is perforated to reduce blistering, center creased for easy angle application and buffed to promote increased adhesion.

RED LABEL PREMIUM WALLBOARD TAPE is made from heavier paper and meets ASTM C-475.

| PROD # | DESC. | SIZE | LGTH. | ROLL/CTN | UNIT | SHIP WT. | UNT./PAL. |
|--------|------------|--------|-------|----------|------|----------|-----------|
| 36260 | Blue Label | 2-1/16 | 500' | 10 | CS | 27 | 85 |
| 36250 | Blue Label | 2-1/16 | 250' | 20 | CS | 26 | 60 |
| 36240 | Blue Label | 2-1/16 | 75' | 20 | CS | 9 | 150 |
| 36030 | Red Label | 2-1/16 | 500' | 10 | CS | 28.5 | 85 |







PREP TEX

- Drywall texture base coat
- Quick dry
- Excellent wet/dry hide
- Superior coverage



| PRODUCT # | 25070 |
|--------------|----------|
| DESCRIPTION | 4.8 Gal. |
| UNIT | Pail |
| SHIP WT. | 65 |
| UNITS/PALLET | 36 |

DRYWALL COMPLETION SYSTEMS

PREP COAT

- Drywall texture base coat
- Achieve Level 5 Finish per ASTM/ GA Standards
- High solids/high build
- Excellent wet/dry hide



| PRODUCT # | 25020 |
|--------------|----------|
| DESCRIPTION | 4.8 Gal. |
| UNIT | PL |
| SHIP WT. | 59 |
| UNITS/PALLET | 36 |

SMOOTH COAT

- Achieve Level 5 Finish per ASTM/ GA Standards
- High solids/high build
- Excellent wet/dry hide



| PRODUCT # | 25080 |
|--------------|----------|
| DESCRIPTION | 4.8 Gal. |
| UNIT | PL |
| SHIP WT. | 65 |
| UNITS/PALLET | 36 |

EZ PATCH LIGHT WEIGHT SPACKLING

- Repairs cracks and holes in one easy application
- Convenient lightweight formula
- Smooth, quick drying and non-shrinking



| PRODUCT # | 55170 | 55180 |
|-------------|----------|---------|
| DESCRIPTION | 1.75 pt. | 3.5 qt. |
| UNIT | 6/CS | 4/CS |
| SHIP WT. | 8/CS | 18/CS |

PATCH & REPAIR

FAST SET 5 FAST SET 20

- Use for taping and patching drywall
- Mixes quickly, easy to sand, non-shrinking





| | Fast Set 5 | Fast Set 20 |
|-------------|------------|-------------|
| PRODUCT # | 55310 | 55330 |
| DESCRIPTION | 4.5 lb. | 4.5 lb. |
| UNIT | 10/bx ctn | 10/bx ctn |
| SHIP WT. | 46/CS | 46/CS |

ACRYLIC AD MIX BONDER

- Formulated for Westpac compounds & textures
- For increased bond to questionable surfaces

MIRACLE MIX

- Increases open time
- Reduces pocking & pinholing



| | Acrylic | Miracle Mix | |
|-------------|------------|-------------|--|
| PRODUCT # | 55140 | 55270 | |
| DESCRIPTION | 1 Gal. | 1 Gal. | |
| UNIT | 4 btls/ctn | 4 btls/ctn | |
| SHIP WT. | 13/ctn | 13/ctn | |



Westpac Materials

The Professional's Choice for Drywall Finishing Products
Proudly Made in the USA

TAPING COMPOUNDS

Taping compounds are designed specifically for embedding paper tape to joints and angles. Extended open time, ease of mixing and the slickness of these products allows the professional applicator to apply tape faster. Westpac Taping Compounds produce maximum bond and provide an excellent base for subsequent top coats.

| PRODUCTS | CATEGORY | SHRINKAGE | TAPING | FIRST METAL | TOP COATS | FASTENER CONCEAL | SANDING |
|---------------|----------|-----------|--------|-----------------|-----------------|------------------|-----------|
| Blue Dot | Taping | High | BEST | Not Recommended | Not Recommended | Not Recommended | Difficult |
| Blue Dot Lite | Taping | Medium | BEST | Not Recommended | Fair | Fair | Fair |

ALL PURPOSE COMPOUNDS

These All Purpose Compounds are approved for all applications associated with drywall finishing. They combine the benefits of our Taping Compounds with our Topping Compounds into one. This enables the applicator to use one mud for all applications.

| PRODUCTS | CATEGORY | SHRINKAGE | TAPING | FIRST METAL | TOP COATS | FASTENER CONCEAL | SANDING |
|------------|-------------|-----------|-----------|-------------|-----------|------------------|-----------|
| Red Dot | All Purpose | High | BEST | Good | Fair | Fair | Difficult |
| White Dot | All Purpose | Medium | Good | Excellent | Excellent | Good | Good |
| TNT* | All Purpose | Medium | Excellent | Excellent | BEST | Excellent | Good |
| TNT Lite* | All Purpose | VERY LOW | Fair | Excellent | Excellent | Excellent | Excellent |
| Hi Lite | All Purpose | Low | Low | Excellent | Excellent | Excellent | Good |
| Super Lite | All Purpose | Low | Low | Good | Good | Good | EASIEST |

^{*}May be special ordered as Eco Finish or Eco Finish Lite with GreenGuard Gold Certification.

TOPPING COMPOUNDS

Topping Compounds are designed specifically for finish coat applications and are not intended for embedding tape. They are formulated for ease of use, low shrinkage and fast sanding.

| PRODUCTS | CATEGORY | SHRINKAGE | TAPING | FIRST METAL | TOP COATS | FASTENER CONCEAL | SANDING |
|----------------|----------|-----------|-----------------|-------------|-----------|------------------|---------|
| Green Dot | Topping | Very Low | Not Recommended | Good | BEST | Best | Easy |
| Green Dot Lite | Topping | LOWEST | Not Recommended | Good | Excellent | Best | Easier |
| Black Dot | Topping | Very Low | Not Recommended | Good | Excellent | Best | EASIEST |

All joint compounds meet ASTM C-475.

WALL TEXURES

Textures are formulated at different solid levels. This chart describes each texture's solids level at an equal viscosity (i.e. thickness). The higher solids level equates to greater stand-out (or more material-heavier texture) on the wall. The lower solids level typically equates to higher mileage (or less stand-out-finer texture).

| HIGH SOLIDS | Blue Line II, Green Line |
|---------------|---------------------------|
| MEDIUM SOLIDS | Green Line II, Black Line |
| LOW SOLIDS | Blue Line, Red Line |

CEILING TEXTURES

Ceiling Textures are formulated with the original coarse aggregate at different ratios to solids. The chart describes each texture's aggregate ratio at an equal viscosity (i.e. thickness). The higher aggregate ratio typically equates to heavier texture appearance. The lower aggregate level typically equates to easier application.

| HIGH AGGREGATE RATIO | Ceiling - Tex Premium |
|----------------------|-----------------------|
| LOW AGGREGATE RATIO | Hopper - Tex |

Westpac Materials 341 West Meats Ave., Orange, CA 92865 | Phone: 714-974-6837 : 866-974-6837 | Fax: 714-637-9033 : 866-637-9033 | www.westpacmaterials.com